

1200Mbps

802.11ac/b/g/n Dual-Band Concurrent 4-Port Gigabit WLAN Router (RE1200R4GC-2T2R-V3i)



WiFi specification

- ◆ Operating Frequency : 2.412G~2.484GHz
- ◆ Operating Frequency : 5.1G~5.8GHz
- ◆ Supports 802.11b data rates of up to 11 Mbps with automatic fallback to 5.5, 2, and 1 Mbps
- ◆ Supports 802.11g data rates of up to 54 Mbps with automatic fallback to 48, 36, 24, 18, 12, 9, and 6 Mbps
- ◆ Support 802.11n (MIMO 2T2R): Up to 300Mbps (MCS15)
- ◆ 802.11ac 2T2R: 866Mbps (5Ghz)
- ◆ Security supports 64/128-bits WEP, WPA, WPA2, WPS
- ◆ Multi-SSID

Ethernet WAN specification

- ◆ WAN: 10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port
- ◆ WAN IP Assignment
 - Static IP
 - DHCP client
 - PPPoE client

LAN specification

- ◆ LAN: 10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port

Features

- ◆ IGMP snooping and IGMP proxy
- ◆ VPN pass through
- ◆ Management - HTTP Web-based Configuration

Hardware interface

- ◆ DC Power jack
- ◆ Power switch to power on /off device
- ◆ Reset button to factory defaults
- ◆ 1 x WAN: 10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port
- ◆ 4 x LAN: 10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port
- ◆ 2 x Antenna
- ◆ WiFi ON/OFF, WPS switch button

Operating Environment

- ◆ Operating temperature: 0 - 45°C
- ◆ Storage temperature: -20 - 70°C
- ◆ Humidity: 20 - 95% non-condensing

